

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
8 February 2001 (08.02.2001)

PCT

(10) International Publication Number
WO 01/10133 A1(51) International Patent Classification⁷: H04N 7/26

(21) International Application Number: PCT/EP00/07425


(22) International Filing Date: 31 July 2000 (31.07.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
99401969.3 3 August 1999 (03.08.1999) EP
99403228.2 21 December 1999 (21.12.1999) EP(71) Applicant (for all designated States except US): KONIN-
KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).[FR/FR]; Prof. Holstlaan 6, NL-5656 AA Eindhoven
(NL). DEL CORSO, Sandra [FR/FR]; Prof. Holstlaan 6,
NL-5656 AA Eindhoven (NL). LE MAGUET, Isabelle
[FR/FR]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).(74) Agent: LANDOUSY, Christian; Internationaal Oc-
trooibureau B.V., Prof. Holstlaan 6, NL-5656 AA
Eindhoven (NL).

(81) Designated States (national): CN, IN, JP, KR, US.

(84) Designated States (regional): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE).Published:
— With international search report.(72) Inventors; and
(75) Inventors/Applicants (for US only): GAUTIER, PierreFor two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.(54) Title: METHOD AND DEVICE FOR ENCODING SEQUENCES OF FRAMES INCLUDING EITHER VIDEO-TYPE OR
FILM-TYPE IMAGES

WO 01/10133 A1

(57) Abstract: The invention relates to the processing of video signals prior to encoding or other compression operations, and, more particularly, to a method for encoding video signals corresponding to a sequence of frames each of which consists of two fields F1 and F2. The proposed method comprises the steps of receiving successive frames of an input video signal and delaying them with at least a "two fields" duration delay, and detecting any dominance change and adjusting said delay. When a change from an F1 dominance to an F2 dominance is detected, the first field of the first F2 dominant frame is suppressed, and said delay is decreased by a quantity equal to "one field" duration; when a change from an F2 dominance to an F1 dominance is detected, the last field of the last F2 dominant frame is repeated, and the delay is further increased by a quantity equal to "one field" duration. The invention also relates to a method for encoding a sequence of frames including either video-type images or film-type images, and to an encoding system that carries out said method by incorporating the first solution hereinabove presented. If a sequence of film-type is detected, the inverse 3:2 pull-down technique is applied on the input frames, while in the opposite case, said technique is de-activated and replaced by said first solution: preprocessing according to the type of dominance change.